

PowerFlex 400 AC Drive

Typical Motor Rating		Input Voltage	Drive Output (A)			Dimensions	Cat No	List Price	
(kW)	(A)		Cont	60 s	3 s	H * W * D			
2.2	9	200-240V 50/60 Hz 3 - Phase	12	13.2	N/A	260*130*180	22C-B012N103	463	
3.7	16		17.5	19.25	N/A	260*130*180	22C-B017N103	561	
5.5	21		24	26.4	N/A	260*130*180	22C-B024N103	640	
7.5	28		33	36.3	N/A	260*130*180	22C-B033N103	776	
11	40		49	53.9	N/A	384*250*205.4	22C-B049A103	985	
15	52		65	71.5	N/A	384*250*205.4	22C-B065A103	1240	
18.5	61		75	82.5	N/A	384*250*205.4	22C-B075A103	1600	
22	72		90	99	N/A	384*250*205.4	22C-B090A103	1900	
30	95		120	132	N/A	384*250*205.4	22C-B120A103	2160	
37	117		145	159.5	N/A	384*250*205.4	22C-B145A103	2700	
2.2	5		380-480V 50/60 Hz 3 - Phase	6	6.6	N/A	260*130*180	22C-D6P0N103	483
3.7	8.4			10.5	11.55	N/A	260*130*180	22C-D010N103	568
5.5	11.4			12	13.2	N/A	260*130*180	22C-D012N103	640
7.5	15	17		18.7	N/A	260*130*180	22C-D017N103	776	
11	22	22		24.2	N/A	260*130*180	22C-D022N103	985	
15	29	30		33	N/A	260*130*180	22C-D030N103	1240	
18.5	34	38		41.8	N/A	384*250*205.4	22C-D038A103	1600	
22	40	45.5		50.05	N/A	384*250*205.4	22C-D045A103	1900	
30	53	60		66	N/A	384*250*205.4	22C-D060A103	2160	
37	65	72		79.2	N/A	589*370*260	22C-D072A103	2490	
45	78	88		96.8	N/A	589*370*260	22C-D088A103	3130	
55	98	105		115.5	N/A	589*370*260	22C-D105A103	3750	
75	132	142		156.2	N/A	589*370*260	22C-D142A103	4540	
90	158	170		187	N/A	589*370*260	22C-D172A103	5360	
110	194	208		228.8	N/A	589*370*260	22C-D208A103	5910	