

Control Techniques SK Inverter Drives

240V Single Phase (0.25 - 2.2kW)

- * Quadratic Motor Flux V/Hz for Fan/Pump
- * IP20 Nema 1 Rating Enclosure
- * 2 Year Warranty
- * Quick & Easy Set-Up
- * Open Loop Flux Vector/Fixed Boost Speed Control
- * Built in EMC Filter
- * Maximum Overload 150% Rated Current for 60secs
- * UL & CE Approval
- * DC Injection Braking as Standard
- * Dynamic Braking Transistor as Standard
- * Field bus Connectivity Option (MODBUS as Standard)
- * Dynamic Motor Flux V/Hz for Energy Saving



Part Number	Frame Size	Supply Volts AC	Rated Amps	kW Rating	Hp Rating	Control Techniques List Price
SKA1200025	A	200/240V 50/60 Hz	1.7	0.25	0.33	£120.00
SKA1200037	A		2.2	0.37	0.5	£125.00
SKA1200055	A		3	0.55	0.75	£140.00
SKA1200075	A		4	0.75	1.0	£150.00
SKBD200110	B		5.2	1.1	1.5	£188.00
SKBD200150	B		7	1.5	2.0	£210.00
SKCD200220	C		9.6	2.2	3.0	£258.00